

TSW SINGLE POLE GROUND AND COUNTERPOISE WIRE - 40% IACS

TSW SINGLE POLE GROUND AND COUNTERPOISE WIRE - 40% IACS												
STANDARD PRODUCTS	AWG	WEIGHT LBS	REEL	STEM FREE	STEM COILS	Diameter Inches	Circular Mils	Pounds per 1000 ft	Nominal Copper Thickness	Ohms Per 1000 Ft	Breaking Load in Pounds	AWG
.257 40% DSA	2	1800	X			0.2576	66358	184.2	0.0193	0.3986	2084	2
		1000		X								
		400			X							
		200			X							
		100			X							
.204 40% DSA	4	1800	X			0.2043	41738	115.8	0.0153	0.6337	1307	4
		1000		X								
		400			X							
		200			X							
		100			X							
		50			X							
		25	X									
.162 40% DSA	6	1800	X			0.162	26244	72.8	0.0121	1.0079	824	6
		1000		X								
		400			X							
		200			X							
		100			X							
		50			X							
		25	X									

Specification: ASTM B 910

Package Capability Descriptions

Stems: Continuous lengths of 500 lbs to 1000 lbs mounted on a pallet and stretched wrapped.

Stems/Coils: Continuous lengths of 50 lbs to 150 lbs string tied loaded on stems & pallet and stretched wrapped.

Coils: Continuous lengths of 50 lbs to 400 lbs string tied and terklesen wrapped and shipped on a pallet.

Reels: Continuous lengths of 100 lbs to 1800 lbs shipped reels, loaded and palletized.

Special Reels: Continuous lengths of 25 lbs to 50 lbs shipped on small spools and palletized to total of 1000 lbs net.

There are not all inclusive but are intended to be a sample of our capability; please discuss exact size ar packaging requirements with us