

Flat Conductor Wire

NOMINAL DIAMETER THICKNESS	FEET PER POUND OF COPPER RIBBON WIRE										
	WIDTH (TOLERANCE +/- .002 MIN.)										
	.020	.030	.040	.050	.060	.070	.080	.090	.100	.110	.120
.002 +/- .0002 MIN.	6,450	*	*	*	*	*	*	*	*	*	*
.002 +/- .0005 MAX.	6,450	4,300	3,225	2,580	2,150	*	*	*	*	*	*
.003 +/- .0002 MIN.	4,300	2,867	*	*	*	*	*	*	*	*	*
.003 +/- .0005 MAX.	4,300	2,867	2,150	1,720	1,433	1,229	1,075	956	860	782	717
.004 +/- .0002 MIN.	3,225	2,150	1,612	*	*	*	*	*	*	*	*
.004 +/- .0005 MAX.	3,225	2,150	1,612	1,290	1,075	921	806	717	645	586	537
.005 +/- .0002 MIN.	2,580	1,720	1,290	1,032	*	*	*	*	*	*	*
.005 +/- .0005 MAX.	2,580	1,720	1,290	1,032	860	737	645	573	516	469	430
.006 +/- .0002 MIN.	2,150	1,433	1,075	860	717	*	*	*	*	*	*
.006 +/- .0005 MAX.	2,150	1,433	1,075	860	717	614	537	478	430	391	358
.007 +/- .0002 MIN.	1,843	1,229	921	737	614	527	*	*	*	*	*
.007 +/- .0002 MAX.	1,843	1,229	921	737	614	527	461	410	369	335	307
.008 +/- .0002 MIN.	1,612	1,075	806	645	537	461	403	*	*	*	*
.008 +/- .0005 MAX.	1,612	1,075	806	645	537	461	403	358	322	293	269
.009 +/- .0002 MIN.	1,433	956	717	573	478	410	358	319	*	*	*
.009 +/- .0005 MAX.	1,433	956	717	573	478	410	358	319	287	261	239
.010 +/- .0002 MIN.	1,290	860	645	516	430	369	322	287	258	*	*
.010 +/- .0005 MAX.	1,290	860	645	516	430	369	322	287	258	235	215
.011 +/- .0002 MIN.	1,173	782	586	469	391	335	293	261	235	213	*
.011 +/- .0005 MAX.	1,173	782	586	469	391	335	293	261	235	213	195
.012 +/- .0002 MIN.	1,075	717	537	430	358	307	269	239	215	195	179
.012 +/- .0005 MAX.	1,075	717	537	430	358	307	269	239	215	195	179

* (Items requiring engineering evaluation.)